

											
Typ		Type		HSS	HSS-TiN	HSS	HSS-TiN	HSS	HSS		
γ		γ		20°	20°	20°	20°	30°	30°		
Zähnezahl		Nombre de dents		3	3	3	3	3	3		
Anwendung		Emploi		siehe technische Hinweise Seite 5				voir recommandations techniques en page 5			
Katalogbezeichnung Désignation de catalogue						VFL-...-...-RAP	VFL-...-...-TiN	VFL-...-...-RAP	VFL-...-...-TiN	VKO-...-...-RAP	VKO-...-...-RAP
D mm	L mm	S mm	Z mm	G mm	Ident. N°						
4.3	46	4	1.6	—	-4.3-1.6-	•	—	—	—	•	—
4.3	46	4	2.2	—	-4.3-2.2-	—	—	—	—	•	—
4.3	46	4	2.5	—	-4.3-2.5-	—	—	—	—	•	—
4.3	46	4	2.6	—	-4.3-2.6-	•	—	—	—	—	—
4.5	46	4	2.0	—	-4.5-2.0-	•	—	—	—	—	—
4.5	46	4	2.5	—	-4.5-2.5-	•	—	—	—	—	—
5.0	55	5	2.0	—	-5.0-2.0-	•	—	—	—	•	—
5.0	55	5	2.5	—	-5.0-2.5-	•	—	—	—	—	—
5.0	55	5	2.7	—	-5.0-2.7-	—	—	—	—	•	—
5.0	55	5	2.8	—	-5.0-2.8-	•	—	—	—	—	—
5.0	55	5	3.1	—	-5.0-3.1-	•	—	—	—	—	—
5.5	55	5	2.5	—	-5.5-2.5-	•	—	—	—	—	—
5.5	55	5	3.0	—	-5.5-3.0-	•	—	—	—	—	—
6.0	55	6	2.5	—	-6.0-2.5-	•	—	—	—	•	—
6.0	55	6	3.0	—	-6.0-3.0-	•	—	—	—	—	—
6.0	55	6	3.2	—	-6.0-3.2-	—	—	—	—	•	—
6.0	55	6	3.6	—	-6.0-3.6-	•	•	—	—	—	—
6.3	55	6	3.2	—	-6.3-3.2-	—	—	—	—	•	—
6.5	55	6	3.0	—	-6.5-3.0-	•	—	—	—	—	—
6.5	55	6	3.5	—	-6.5-3.5-	•	—	—	—	—	—
6.5	55	6	4.0	—	-6.5-4.0-	•	—	—	—	—	—
6.6	55	6	2.5	—	-6.6-2.5-	—	—	—	—	•	—
6.6	55	6	3.2	—	-6.6-3.2-	—	—	—	—	•	—
6.6	55	6	3.6	—	-6.6-3.6-	—	—	—	—	•	—
7.0	70	6	—	M 3	-7.0-M3-	—	—	•	•	—	•
7.2	70	6	—	M 3	-7.2-M3-	—	—	•	•	—	—
7.5	70	6	—	M 3	-7.5-M3-	—	—	•	•	—	—
8.0	70	6	—	M 3	-8.0-M3-	—	—	•	—	—	—
8.5	70	6	—	M 3	-8.5-M3-	—	—	•	—	—	—
9.0	70	6	—	M 3	-9.0-M3-	—	—	•	—	—	—
9.5	70	6	—	M 3	-9.5-M3-	—	—	•	—	—	—

Andere Abmessungen teilweise ab Lager

Autres dimensions en partie du stock

Bestell-Nr.: Ident.-N° in Katalogbezeichnung einfügen
z. B.: VFL-4.3-1.6-RAP

N° de commande: Introduire Ident. N° dans la désignation de catalogue
par exemple: VFL-4.3-1.6-RAP

